


F connector female to female keystone coupler



F connector female to female keystone coupler (KCFbk/wh)

This module can be used to extend an F-connection. With its standardised dimensions, it can be used for easy snap-in mounting in e.g. a keystone patchpanel, face plate or surface-mount box.

Features





- Connector: F female to F female
- Impedance: 75 Ohm
- Easy screw connector on both sides
- Ideal for satellite installations

Specifications


- Dimensions: 25.5 x 16.3 x 22.3mm (LxWxH)
- Colour: Black or White
- Materials:
Connector body: Nickel-plated zinc
Keystone mount/ Housing: Fire retardant ABS UL 94V-0
- Weight: 6g approx.
- Length in front of the panel: 8.1 mm
- Packaging: Supplied in individual polythene bags, then in bags of 20.

EAN Numbers: KCFbk - 5055386507020; KCFwh - 5055386507037


Code: **KCFBk**
KCFWh



Nickel-plated Zinc



Fireproof ABS UL-94V0

DRAW NO:		ITEM NO:	
	APPR	CUSTOMER:	
UNIT: m/m	DESIGN	DATE:	
SCALE:	Ref. NO:	TOLERANCE:	· ± 1 · X ± 0.2 · XX ± 0.15
TUK Ltd			

All measurements are in mm