

Category 6 Connection Boxes



Category 6 Connection Boxes (S78Wh+S78Bk)

Features:


- Full compliance with Category 6 standard performance requirements for a consolidation point
- Quick release lid
- Robust outer casing
- Patented cable retention clip
- Supplied with fixing screws and adhesive pad for optional mounting
- IDC's - industry standard 'Krone LSA+' type suitable for 26 to 24 AWG (0.405 to 0.511mm) solid or stranded cable (with outer diameter 1mm \pm 0.05)

Specifications:

DIMENSIONS (mm): 55 x 35 x 24.5 approx

Materials:

- Outer casing: ABS
- Contacts: Nickel over copper
- PCB: FR4
- Colour: Black or White



Category 6 Connection Box Shielded



Category 6 Connection Box Shielded (S78Sv2)

Features:


- Full compliance with Category 5e & 6 standard requirements for a consolidation point
- Quick release lid (with use of a screwdriver)
- Robust outer casing
- Supplied with fixing screws and adhesive pad for optional mounting
- IDC's - industry standard 'Krone LSA+' type

Specifications:

DIMENSIONS (mm): 63 x 33 x 28.7 approx

Materials:

- Outer casing: ABS electroplated
- Contacts: Nickel over copper
- PCB: FR4
- Colour: Silver



TUK Ltd, Unit 4, Wimbledon Stadium Business Centre, Riverside Road, London, SW17 0BA