


Category 6 Keystone Mount Coupler



Category 6 Compact Keystone Mount Coupler (SACK4)

Features

- Designed to fit US industry standard keystone mount outlets wall plates and patch panels
- High performance data throughput, meets Category 6 data transfer rates
- Category 5e versions also available

Specifications

- Dimensions: **SACK4:** 29.5x16.9x19.25 mm **SACK4bk#24:** 280x70x35mm
- Weight: **SACK4:** 6 grams **SACK4bk#24:** 138 grams
- Housing: ABS UL94V-0
- Contacts: 50µ"/1.27µm gold plating over nickel plated phosphor bronze
- Colour: Black (SACK4bk) and White (SACK4wh)
- Operating temperature: -40°C to 66°C (-40°F to 150°F)

Packaging:

- Standard product is supplied in individual polythene bags. To save time for panel assemblers, SACK4bk#24 is available as a "bulk pack" of 24 pieces without individual bags.


Commodity Code: 85444920

EAN Number: SACK4bk/wh – 5055386507648/5055386507716

SACK4bk#24 – 5055386507655

ROHS Compliant

Code: SACK4bk/wh



ELECTRICAL

CURRENT RATING: 1.5A.

DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC 60Hz.

INSULATION RESISTANCE: 500M Ω MIN.

CONTACT RESISTANCE: 20m Ω MAX.

MECHANICAL

(1) Materials: ABS+PC V0

(2) RJ45 Jack Contact: 50 μ m/1.27 μ m gold plating over nickel plated phosphor bronze